



TRS-R/825x225

## TYPE TRS-R

[Configure now](#)

### VENTILATION GRILLES, MADE OF GALVANISED SHEET STEEL, WITH INDIVIDUALLY ADJUSTABLE, VERTICAL BLADES, FOR INSTALLATION INTO CIRCULAR DUCTS

Ventilation grille with droplet shaped blades

- Nominal sizes 225 x 75 – 1225 x 225 mm
- Volume flow rate range 11 – 930 l/s or 40 – 3348 m<sup>3</sup>/h
- Grille face made of galvanised sheet steel
- Front border with countersunk holes, 27 mm wide

Optional equipment and accessories

- Grille face in RAL CLASSIC colours
- Attachments for volume flow rate balancing and air direction control

## Application



### Application

- Ventilation grille of Type TRS-R as supply air or extract air variant for comfort zones and industrial zones
- Directed supply air discharge for mixed flow ventilation
- Blades are adjustable to meet different local requirements
- For variable and constant volume flows
- For supply air to room air temperature differences from –12 to +4 K
- For installation into circular ducts

### Special characteristics

- Individually adjustable blades

### Nominal sizes

- Nominal length: 225, 325, 425, 525, 625, 825, 1025, 1225 mm
- Nominal height: 75, 125, 225 mm

Other dimensions upon request

## Description



### Variants

- TRS-R-RA: Grille face with vertical blades
- TRS-R-RD: Grille face with vertical and horizontal blades, individually adjustable

### Parts and characteristics

- Sloped border with chamfered inside edge
- Individually adjustable, vertical blades
- Factory fitted perimeter seal
- RD: Individually adjustable, horizontal blades for air direction control

### Attachments

- RS, R5: For volume flow rate balancing

#### Construction features

- Asymmetrically supported blades
- Front border with countersunk holes

Suitable circular duct diameter

- H = 75 mm: Ø150 – 400 mm (with attachment -5 and L from 825 mm: Ø224 – 400 mm)
- H = 125 mm: Ø300 – 900 mm
- H = 225 mm: Ø600 – 2400 mm

#### Materials and surfaces

- Border and blades made of galvanised sheet steel
- P1: Border and blades powder-coated, RAL CLASSIC colour

#### Standards and guidelines

- Sound power level of the air-regenerated noise measured according to EN ISO 5135

#### Maintenance

- Maintenance-free as construction and materials are not subject to wear
- Inspection and cleaning to VDI 6022

#### TROX Austria GmbH

---



Lichtblaustraße 15  
1220 Wien, Austria

Telefon +43 1 250 43-0  
Fax +43 1 250 43-34  
E-Mail: [trox-at@troxgroup.com](mailto:trox-at@troxgroup.com)

#### Online-Services

---

- › [TROX Academy](#)

---

- › [Your contact partner](#)

---

- › [Online fault report](#)

---

#### Service-Hotlines

---

Sales Austria  
and technical consulting  
+43 1 250 43 0  
[Contact](#)

#### TROX IN SOCIAL WEB

---